LABEL FACE FILMS Printable Topcoated Polyester Films for VIP

Item number:

A03650

Description:

Matte Silver 36 micron (1.5 mil) polyester film with matte topcoat for excellent ink and toner adhesion and durability.

Suitable for printing with:

- Laser
- Thermal transfer (subject to ribbon compatibility)
- Xeikon™
- All conventional printing processes

Applications:

- Labels that need to withstand exposure to water, steam, oil or chemicals.
- Labels with high-resolution barcodes variable information added by end user.

Product Specifications:

PROPERTY	TEST METHOD	A03650	
Appearance		Matte silver	
Thickness	-	43 ± 3 1.4	[micron] [mil]
Area Yield	-	17.9 12.6	[m²/kg] [msi/lb]
Base Film Haze	ASTM D-1003	1.2 ± 0.2	[%]
Tensile Strength	ASTM D-882	MD 21 ± 5 29800 ± 7100	TD 21 ± 5 [Kgf/mm ²] 29800 ± 7100 [psi]
Elongation at Break	ASTM D-882	MD 140 ± 50	TD 120 ± 30 [%]
Shrinkage	After 30 minutes at 150 °C	MD 1.5 ± 1.0	TD 0.5 ± 0.5 [%]









LABEL FACE FILMS Printable Topcoated Polyester Films for VIP

DS No=2105/5, Page 2 of 2, October 2018

DISCLAIMER - All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

©2018 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation and/or its Affiliates. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

AVERY DENNISON

