LABEL FACE FILMS Printable Topcoated Polyester Films

Item number:

A05073

Description:

Glossy Silver 50 micron (2 mil) polyester film with mirror-like appearance, with print primer to optimize adhesion of printing inks and increase scuff resistance.

Suitable for printing with:

- Rotogravure
- **UV** Flexography
- **UV** letterpress
- Silk screen
- **UV** Inkjet
- Thermal transfer (subject to ribbon compatibility)

Applications:

- Labels and tags
- Stickers, decals
- Graphic displays

Product Specifications:

PROPERTY	TEST METHOD	A05073	
Appearance		High Gloss Silver	
Thickness	-	50 ± 2 2	[micron] [mil]
Area Yield	-	14.1 9.9	[m²/kg] [msi/lb]
Base Film Haze	ASTM D-1003	<1 ± 0.2	[%]
Tensile Strength	ASTM D-882	MD 22 ± 4 31300 ± 5600	TD 26 ± 4 [Kgf/mm ²] 36900 ± 5600 [psi]
Elongation at Break	ASTM D-882	MD 190 ± 50	TD 130 ± 50 [%]
Shrinkage	After 30 minutes at 150 °C	MD 1.5 ± 0.5	TD 0.5 ± 0.4 [%]





LABEL FACE FILMS Printable Topcoated Polyester Films

DS No=21124, Page 2 of 2, August 2018

All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, available at http://terms.europe.averydennison.com

©2018 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation and/or its Affiliates. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.



