

LABEL FACE FILMS

Dry Erase Polyester Film

*Preliminary Information**

Item number:

K02306S

Description:

23 micron UV stabilized clear Polyester film with a proprietary dry erase coating, suitable for lamination to PVC or metal coil.

Applications:

Dry-erase boards, menu boards

Benefits:

- Wipe clean surface suitable for standard Expo®-type dry erasable marker or "liquid chalk"
- High chemical resistance
- Retains high gloss, clarity and dimensional stability also in exterior use

Product Specifications:

*Product is under development and values are based on preliminary results.

PROPERTY	TEST METHOD	K02306S	
Appearance		Clear	
Thickness	-	23	[micron]
UVT (300-380 nm)	ASTM E903-96	≤ 0.5	[%]
Area Yield	-	13.6	[m ² /kg]
Tensile Strength	ASTM D-882	MD 18	TD 20 [Kgf/mm ²]
Elongation at Break	ASTM D-882	MD 160 ± 40	TD 140 ± 40 [%]
Shrinkage	After 30 minutes at 150 °C	MD 1.0	TD 0.5 [%]



LABEL FACE FILMS

Dry Erase Polyester Film

*Preliminary Information**

DS No=2600/1 Page 2 of 2, October 2018

DISCLAIMER - All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2018 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation and/or its Affiliates. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

Avery Dennison Israel Ltd
Kibbutz Hanita, 2288500 Israel
T: +972 4 985 9919
E: hanita.coatings@eu.averydennison.com

