LABEL FACE FILMS Printable Topcoated Polyester Films for VIP

Item number:

K03604

Description:

Clear 36 micron (1.5 mil) polyester film with matte topcoat to optimize ink and toner adhesion and durability.

Suitable for printing with:

- Rotogravure
- UV Flexography
- Silkscreen
- UV Inkjet
- Thermal transfer (subject to ribbon compatibility)

Applications:

- Labels
- Printable over-laminate

Product Specifications:

PROPERTY	TEST METHOD	K03604	
Appearance	-	Matte translucent	
Thickness		44 ± 1.2 1.75	[micron] [mil]
Area Yield	-	17.7 12.5	[m²/kg] [msi/lb]
Base Film Haze	ASTM D-1003	± 0.5	[%]
Tensile Strength	ASTM D-882	MD 25 ± 4 35600 ± 5600	TD 26 ± 4 [Kgf/mm ²] 36900 ± 5600 [psi]
Elongation at Break	ASTM D-882	MD 140 ± 50	TD 120 ± 50 [%]
Shrinkage	After 5 minutes at 190 °C	MD 1.5 ± 1.0	TD 0.5 ± 0.5 [%]









LABEL FACE FILMS Printable Topcoated Polyester Films for VIP

DS No=2105/1, Page 2 of 2, January 2019

DISCLAIMER - All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see http://terms.europe.averydennison.com

©2018 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation and/or its Affiliates. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

Avery Dennison Israel Ltd Kibbutz Hanita, 2288500 Israel T: +972 4 985 9919

E: hanita.coatings@eu.averydennison.com www.hanita.averydennison.com



