

LABEL FACE FILMS

Printable Topcoated Polyester Films for Laser Printing

Item number:

K05071U

Description:

White 50 micron polyester label face film with a proprietary dry toner receptive topcoat for monochrome and color laser printers and copiers.

Applications:

- Digital labels and tags
- Stickers

Suitable for printing with:

- Color laser printers
- B & W laser
- Copiers

Product Specifications:

PROPERTY	TEST METHOD	K05071U	
Appearance	-	Glossy White	
Thickness	-	51 ± 3 2	[micron] [mil]
Area Yield	-	14 9.8	[m ² /kg] [msi/lb]
Tensile Strength	ASTM D-882	MD 16 22700	TD 18 [Kgf/mm ²] 25600 [psi]
Elongation at Break	ASTM D-882	MD 130	TD 100 [%]
Shrinkage	After 5 minutes at 190 °C	MD 2	TD 0.5 [%]



RoHS
compliant



Halogen free

LABEL FACE FILMS

Printable Topcoated Polyester Films for Laser Printing

DS No=2107/3 , Page 2 of 2, August 2018

DISCLAIMER - All Avery Dennison statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. All Avery Dennison products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes. All Avery Dennison's products are sold subject to Avery Dennison's general terms and conditions of sale, see <http://terms.europe.averydennison.com>

©2018 Avery Dennison Corporation. All rights reserved. Avery Dennison and all other Avery Dennison brands, this publication, its content, product names and codes are owned by Avery Dennison Corporation and/or its Affiliates. All other brands and product names are trademarks of their respective owners. This publication must not be used, copied or reproduced in whole or in part for any purposes other than marketing by Avery Dennison.

Avery Dennison Israel Ltd
Kibbutz Hanita, 2288500 Israel
T: +972 4 985 9919
E: hanita.coatings@eu.averydennison.com
www.hanita.averydennison.com

